



## GSA SPEED COAT GAP FILLER

### Description

A super-fast drying gap filler that can be painted over in 15 minutes. Speed coat has low shrinkage and excellent resistance to paint cracking.

**Key Performance Properties:** Formulated for sealing and filling gaps for time sensitive jobs. Can be painted over in 15 minutes. (@25°C / 50%RH)

**Application:** For sealing and filling gaps and cracks where movement occurs such as those between plaster work, window frames, door frames and skirting boards.

### Specification

Tooling Time: 5 minutes

Ready for painting: 15 minutes

Cure time: 48 hours

Joint movement: 10%

**Directions:** Make sure surfaces are clean, dust and grease free. Cut the cartridge seal and screw on nozzle which should be cut to your required size. Using a caulking gun, apply sealant into the gap or joint ensuring a good solid fill. Smooth if required using a putty knife or wet sponge. Remove any excess immediately with a wet cloth. Sealant should be touch dry in approximately 15 minutes. After use, clean tools with water. Cured sealant can be trimmed with a knife.

**Painting:** Speed Coat can be painted over with emulsion paint after 15 minutes. Test paint on a small section of the sealant. Cracking may occur on paints that shrink during drying process (some water-based undercoats and flat paints) . Paint cracking can be reduced by applying a vinyl or semi-gloss acrylic or oil-based undercoat first or allow the sealant to fully cure before painting. When coating with oil-based paints allow 48 hours before painting. Allow 120 mins before coating with a ceiling paint or flat emulsions.

**Packaging:** Cartridge: 450g Carton: 20

**Storage and shelf life:** Store between 5°C and 25°C in cool dry conditions. Protect from low temperatures and frost. Shelf life 24 months.

**Limitations:** Do not apply in wet or damp conditions, below 5°C or below ground level. Not recommended for joints where directly exposed to water or where water pools. Not suitable for fine joints in tongue and groove boards or weatherboard overlaps. Painting will improve exterior durability. To avoid paint cracking, apply only to gaps no larger than 5mm deep and 10mm wide.

**Health and safety:** Non-hazardous product. Keep away from children and animals. Do not take internally, keep out of eyes. If contact with skin, wash with soap and water.

**First Aid:** Please refer to the Safety Data sheet which is available at [www.cwbrands.com.au/](http://www.cwbrands.com.au/)





## GSA SPEED COAT GAP FILLER

### Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.