



GSA EXPANDING FOAM

Description

GSA expanding Foam is a one component, multi-purpose polyurethane foam for general purpose applications in filling, sealing, insulating and soundproofing. The straw adapter included with each can aids in easy application, especially to fill gaps of all dimensions in the most difficult locations. Can be used for both interior and exterior applications.

Application: Ideal for filling gaps around window frames, door frames, wall panels and filling awkward gaps/ holes in construction applications. It greatly reduces noise, dust and draughts, and blocks access by rodents. The foam has powerful adhesive properties, bonds well to timber, brick, concrete, steel, aluminium, glass, fibre cement sheet and plasterboard.

Specification

Colour: Light Yellow
 Appearance: Foam
 Slump: None
 Sandable: After Curing
 Paintability: After fully cured
 Full Expansion: 60 Minutes
 Fully Cured: 3 Hours
 Tack Time: 10 Minutes
 Expansion: Approximately 3 times

Surface Preparation: Surface must be clean and free from grease, oil, loose particles.

Directions: Moisten surfaces with water to aid the expansion process. Shake can vigorously before use. Carefully screw the applicator nozzle onto the valve. Hold can upside down and extrude the foam by depressing the nozzle. Foam will expand over time. It can be cut, sanded, plastered, or painted over once cured.

Packaging : Available in 300 ml, 500ml and 750 ml aerosols
 12 cans per carton 1152 cans per pallet

Storage/Shelf Life

Best stored between 5°C and 25°C in a cool, dry and well-ventilated storage space. Do not store in direct sunlight. Shelf life is 18 months from manufacturing date.

Health & Safety: Ensure the appropriate safety equipment is worn. Disposable gloves are provided with each can. Be sure the work site has adequate ventilation.

First Aid

Please refer to the Safety Data Sheet which is available at www.cwbrands.com.au/

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.

