


ARDEX A 46

External Patching Compound

ARDEX A 46 is a rapid setting and drying slump-free mortar. Easy to use ARDEX A 46 mixes and trowels easily and gives a smooth finish on both walls and floors. The exceptional hardness and shrinkage free finish of ARDEX A 46 is ideal for creating new ramps, forming coves, patch repairs, stairs, making good around penetrations and filling cracks. **LOW VOC** 

LOCATION

- External and internal
- Above or below grade application

SUBSTRATES

- New and existing concrete, moist or dry

COATINGS

- Polyurethane coatings
- Epoxy coatings
- Membrane coatings
- Ceramic and quarry tiles

COVERAGE

- Approximately 1.4kg powder/mm/m²

THICKNESS

- 2 - 30mm in one application

DRYING TIME

- Walkable in 2 - 3 hours
- Ready for tile or floor coverings from 24 hours
- Coatings from 48 hours

PACKAGING

- 20kg triple layered bag

CODE

25354



ARDEX A 46 QUICK FACTS

- For external repairs to concrete floors, walls and stairs
- Ideal for smoothing surfaces and forming ramps
- Quick drying - trafficable after 2 - 3 hours
- Easy to install - 2mm to 30mm in one application



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE