


WATERPROOFING

ARDEX WPM 155 *Rapid Plus*

Professional Engineered Undertile Membrane

ARDEX WPM 155 Rapid Plus is a water-based polyurethane-acrylic hybrid waterproofing membrane developed for high performance undertile waterproofing. **LOW VOC** 

- Express dry time with bathroom tiling possible in just 4 hours, with no risk to corners and junctions
- Crack Isolation protection over shrinkage, hairline and other non-structural cracks
- Tough flexible film
- Can be tiled over – good adhesion with ARDEX tile adhesives
- STB Tape eliminates need for bond breaker
- Class III Membrane, as per AS/NZS 4858 Wet Area Membranes

LOCATION

- Internal and external.

SUBSTRATES

- Concrete, renders and screeds, fibre-cement sheets and wet area plasterboard, plywood.

COVERAGE

- A 20kg unit (15L) will cover approximately 17.5m².
- A 5.3kg unit (4L) will cover approximately 4.6m².

COLOURS

- Blue

DRYING TIME

- First coat should be applied at 0.5mm (wet film thickness) to provide a 0.25mm dry film thickness. Dry time is approximately 1-2 hours
- Second coat at 0.5mm (wet film thickness) to provide a dry film thickness of 0.25mm. This will provide a total dry film thickness of 0.5mm.

PACKAGING

- 4L (5.3kg)
- 15L (20kg) pails

CODE

- 38792
- 38790



ARDEX WPM 155 *Rapid Plus*

QUICK FACTS

- Express dry time
- Crack isolation protection
- Excellent adhesion with ARDEX tile adhesives
- ARDEX STB Tape eliminates need for bond breaker



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE