

Description

Gripset Xpress SP is a solvent free primer specifically developed with adhesion enhancing properties for non-porous, dense and smooth substrates. It is designed for use on both wall and floor surfaces, achieving high adhesion without the need for etching or using solvents. Ideally suited for the application of Gripset self-adhesive sheet and liquid membrane systems to enable the bond to difficult substrates. Also suitable for porous surfaces.



Features & Benefits

- Solvent free alternative to dangerous solvent based primers
- Bonds to a variety of metal, plastic, glazed, smooth & dense surface
- Suitable on porous surfaces
- Super adhesion properties
- Ease of application
- Low dirt retention, non-tacky
- Suitable for internal and external applications
- Sprayable
- Time saving, user friendly and environmentally safe

Application

Gripset Xpress SP is suitable for commercial, industrial and residential applications.

Substrates

- Metals including: galvanised iron, zincalume, aluminium, stainless steel, copper, brass treated steel, colorbond sheeting
- Precast and tilt up concrete, glass reinforced concrete
- Hardwood and dense timber surfaces
- Existing ceramic tiles, vitrified tiles and natural stone
- Brickwork (clay and concrete)
- Compressed cement sheeting, plasterboard surfaces
- James Hardie™ Scyon™ Secura™ external/internal flooring
- Polymer mortars, synthetic mortars, smooth self-levelling compounds
- Marine plywood and timber sheet surfaces
- Glazed surfaces
- Rigid plastic surfaces
- General surfaces where absorbing primers are not suitable or where adhesion enhancement is required

Surface Preparation

Surfaces must be prepared thoroughly before commencing application. All substrates must be structurally sound, smooth, stable, dry, and clean.

Rough surfaces and voids to be evened or filled first and all brick/block surfaces to be pointed flush. (refer to Gripset 11Y for concrete/masonry repairs). All general surface defects to be repaired.

Building surfaces must be constructed to manufacturer's recommendations and relevant building standards in force at time of product application.

All surfaces are to be free of sharp protruding objects, loose material, de-bonded coatings, curing membranes/agents, release agents, wax residues, foreign particles, laitance, algae and moss, grime, oils, animal fats or grease remains.

Structurally unsound layers and surface contaminants are to be mechanically removed by abrasive blasting, blast tracking, grinding or equivalent methods.

Application and Coverage

- Stir product well before using and apply product using a low nap roller or long bristle brush. Ensure coverage is even to the surface being treated. Contact Gripset Technical Services for details on spray application.
- On smooth, non-porous surfaces, such as metal, glass reinforced concrete, glazed tiles, a minimum coverage of 1 litre/12m² is required. Depending on the absorbency and nature of the surface, coverage of up to 1 litre/m² may be required.

Coverage may vary due to porosity of substrate.

Storage conditions

- Best stored at room temperature.
- Avoid cold freezing conditions and off concrete floors.
- Do not store in direct sunlight.
- Shelf life: 24 months in unopened container

Packaging

- 1 Litre and 10 Litre pails

Precautions

- Not to be used as primer for areas with rising moisture or negative hydrostatic pressure
- Not to be used in immersed applications
- Safety Data Sheet (SDS) available
- For further information about this product contact technical department of Gripset Industries.

Clean up

- In water while wet
- Once dried product needs to be removed mechanically or by solvent
- On hands or skin while product is wet – use soap and water.
- Once cured use solvent free hand cleaners.

TECHNICAL DATA

Form	Viscious Liquid
Colour	Wet/Dry – off white, not opaque
Specific gravity	1.24g/cm ³
pH	7.0-8.5
Drying time	30 mins @ 23°C & 50% RH
Viscosity	4000 mPas
Adhesion properties	
- Concrete	> 1.23MPa
- Glazed tiles	0.83MPa
- Hardies Scyon™	0.8MPa
- Particle board wet area grade	0.6 MPa (failure within timber surface)
VOC Content (ISO 13741-1)	Nil
The VOC Content of Gripset Xpress SP is below the maximum VOC Content for Architectural and Interior Sealants as required by Green Star Ratings tools Education v1, Healthcare v1, Industrial v1, Multi Unit Residential v1, Office Interiors v1.1, Office Design v2, Office v3, Office As Built v2 and Retail Centre v1	

Product Disclaimer

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Gripset Industries does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

Notes

It is recommended before commencing the application; that adhesion of products to be used (e.g. primers, membranes, coatings adhesives etc) is tested over a typical area of the prepared surface to ensure satisfactory adhesion. It is the responsibility of the applicator to carry this out and accept the substrate suitability before any application starts. Gripset Industries offers a service for pre testing adhesion to surfaces for large commercial areas or unusual substrates. For further details contact Gripset Industries. Details contained in product data sheets are general. For any situation or items not covered in this data sheet, it is the responsibility of the applicator to check with Gripset Technical Services before commencing the application. A written confirmation will then be issued by Gripset Technical Services.

Gripset Industries Pty Ltd

ABN: 64 137 930 093
Telephone: +61 (8) 8124-7300 or 1800 650 435
Email: techenquiries@gripset.com
Website: www.gripset.com