

VOC Content Test Certificate

Thursday 05th November 2020

Supplier: Kerakoll Asia Pacific (88 Sutton Street, North Melbourne, VIC, 3051, Australia).

Sample Description: BIOFLEX® S1 ZERO

Date Tested: October 2020 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3690-05 Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings. ASTM D3960 as detailed for paints as well as South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

| _ | | • • | • | | | |
|----|----|-----|-----|----|--------------|---|
| C. | 20 | cit | ica | +1 | \mathbf{a} | n |
| J | ノヒ | u | ıva | u | v | |

Green Building Council of Australia Green Star Design & As Built V1.3-13.1.1B Green Star Interiors V1.3-12.1.1B

BIOFLEX® S1 ZERO

General Purpose adhesives and sealants: 50 grams per Litre

<1 grams per Litre as VOC content per material

We hereby certify that BIOFLEX® S1 ZERO is below the VOC Content limits of chosen categories specified by Green Star Design, Green Building Council of Australia

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Tuan Duong BE (Chem. Eng.)

Consultant

h.S. Si Conth Srikanth C. Srivatsa PhD (Chemistry)

Consultant

V2010061