



Aquaprime SB Primer

Solvent Based Primer for Acrylic Membranes

Features

- ▶ Primer / Sealer
- ▶ Water Based
- ▶ Excellent Adhesion
- ▶ Fast Curing
- ▶ No Thinning Required

Product Description

Aquaprime SB Primer is a one part acrylic primer used to prime and seal concrete substrates. It cures to form a water resistant coating having excellent adhesion to sound concrete, plywood etc. **Aquaprime SB Primer** is an excellent primer for acrylic membrane where the substrate surface is in poor condition i.e. chalky, powdery etc.

Features & Benefits

- Primer for water-based membranes
- Excellent adhesion
- Penetrating primer
- Fast curing
- Easy to apply

Uses

- Primer for water based membranes
- Sealing of concrete floors

APPLICATION INSTRUCTIONS

Substrate Preparation

- All surfaces must be clean, sound and free from dust, oil, rust, cement droppings, protrusions, old sealant or any other contamination. Surfaces must also be free from form release and curing agents.
- Metal surfaces shall be clean and free of any rust, dirt, grease and oil. Rusted surfaces must be wire brushed or sandblasted and treated with an appropriate rust converter.

Application

1. Apply the first coat of **Aquaprime SB** to the entire area that needs to be waterproofed using a roller, brush or spray and allow to cure.
2. Apply at rate of 6-8m² per litre
3. Time between coats if required, 3 days. at 20°C



Aquaprime SB Primer

Solvent Based Primer for Acrylic Membranes

Precautions

- Do not apply product if temperature is in excess of 35°C or less than 5°C.
- Do not apply if relative humidity is above 85%.
- Ensure product is fully cured prior to membrane application.
- Do not apply product if rain is imminent.
- Do not use under Polyurethane Membranes.

Coverage

- Apply **Aquaprime SB** at a rate of 6 – 8m² per litre.

Curing

- Full Cure: 30 - 60 minutes @ 25°C
- Can be recoated after several days
- Minimum cure temperature 10°C

Clean Up

Tools and excess product can be cleaned with water while still wet. Cured material may be removed by mechanical means and the use of **Pasco Xylene**.

Packaging

Aquaprime WB Primer is available in:

- 4 Litre
- 20 Litre

COLOUR

Aquaprime WB Primer is available in clear.

Shelf Life

12 months minimum, when stored in cool, dry, original containers in conditions below 25°C.

Health and Safety

Keep out of reach of children. Wear suitable protective clothing, gloves and eye/face protection. Uncured sealant may cause skin, eye and respiratory system irritation. Use only in well ventilated areas.

In case of contact with eyes, rinse immediately with plenty of water and contact a Doctor or Poisons Information Centre (**Ph 13 11 26**). In case of skin contact, wash affected area with hand cleaner followed by soap and water.

Material Safety Data Sheets must be read and understood prior to using the product.

Pasco Construction Solutions Pty Ltd offers its' products for sale, subject to its standard terms and conditions of sale, which are available upon request. All endeavors have been made to ensure the information provided in this technical data sheet is accurate and correct, however as the use of this material is beyond the supplier's control, liability is limited to replacement of material proven faulty. It is the responsibility of the purchaser to ensure that the product is suitable for the specific application and that it is applied in accordance with the supplier's recommendations.



241 Ingles Street
Port Melbourne, VIC 3207
Ph: (03) 9429 9111

4/14 Tennyson Road
Gladesville, NSW 2111
Ph: (02) 9817 4441